

## Cable connector - CA-19P1N128008S - 1619478

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)



Cable connector, straight, shielded: yes, SPEEDCON locking, M23, Number of positions: 16+3, Type of contact: Male connector, Solder connection, Cable diameter: 10 mm ... 14.5 mm

The figure shows the 12-pos. product version

### Product Features

- Safe use in the field, thanks to high degree of protection
- Connector for flexible on-site assembly
- Consistent EMC protection for reliable transmission of signals
- Reduced connection time with SPEEDCON fast locking system
- Solder connection: proven connection technology for various litz wires



### Key Commercial Data

|                      |          |
|----------------------|----------|
| Packing unit         | 1 pc     |
| Custom tariff number | 85366990 |
| Country of origin    | Germany  |

### Technical data

#### Temperature range

|                                 |                   |
|---------------------------------|-------------------|
| Ambient temperature (operation) | -40 °C ... 125 °C |
|---------------------------------|-------------------|

#### Data of the insulating body

|                           |                   |
|---------------------------|-------------------|
| Coding                    | N                 |
| Insulator material        | PA 66             |
| Contact material          | CuZn              |
| Contact surface material  | Ni/Au             |
| Contact connection method | Solder connection |
| Type of contacts          | Male connector    |

## Cable connector - CA-19P1N128008S - 1619478

### Technical data

#### Data of the insulating body

|   |                      |
|---|----------------------|
| Number of positions                             | 19                   |
| Contact diameter of power contacts              | 1.5 mm               |
| Litz wire cross section of power contacts min.  | 0.08 mm <sup>2</sup> |
| Litz wire cross section of power contacts max.  | 1 mm <sup>2</sup>    |
| Nominal current per power contact at 25°C       | 10 A                 |
| Nominal voltage, power contact                  | 150 V                |
| Contact diameter of signal contacts             | 1 mm                 |
| Litz wire cross section of signal contacts min. | 0.08 mm <sup>2</sup> |
| Litz wire cross section of signal contacts max. | 1 mm <sup>2</sup>    |
| Nominal current per signal contact at 25°C      | 8 A                  |
| Nominal voltage, signal contact                 | 150 V                |
| Overvoltage category                            | II                   |
| Degree of pollution                             | 3                    |

#### Housing data

|  |                  |
|--|------------------|
| Housing material                       | CuZn, GD-Zn      |
| Type of locking                        | SPEEDCON locking |
| Degree of protection (when plugged in) | IP67             |
| Thread type                            | M23              |

#### Cable seal data

|                     |         |
|---------------------|---------|
| Min. cable diameter | 10 mm   |
| Max. cable diameter | 14.5 mm |
| Sealing material    | NBR     |

### Classifications

#### eCl@ss

|            |          |
|------------|----------|
| eCl@ss 4.0 | 272607xx |
| eCl@ss 4.1 | 272607xx |
| eCl@ss 5.0 | 27260701 |
| eCl@ss 5.1 | 27260701 |
| eCl@ss 6.0 | 27260702 |
| eCl@ss 7.0 | 27440102 |
| eCl@ss 8.0 | 27440102 |

#### ETIM

|          |          |
|----------|----------|
| ETIM 3.0 | EC001121 |
|----------|----------|

# Cable connector - CA-19P1N128008S - 1619478

## Classifications

### ETIM

|          |          |
|----------|----------|
| ETIM 4.0 | EC002635 |
| ETIM 5.0 | EC002635 |

### UNSPSC

|               |          |
|---------------|----------|
| UNSPSC 6.01   | 43172015 |
| UNSPSC 7.0901 | 43201404 |
| UNSPSC 11     | 43172015 |
| UNSPSC 12.01  | 43201404 |
| UNSPSC 13.2   | 43201404 |

## Approvals

### Approvals


#### Approvals


UL Recognized / cUL Recognized / EAC / cULus Recognized

#### Ex Approvals

#### Approvals submitted

## Approval details

|   |       |
|---|-------|
| UL Recognized  |       |
| mm <sup>2</sup> /AWG/kcmil  | 18    |
| Nominal current I <sub>N</sub>  | 8 A   |
| Nominal voltage U <sub>N</sub>  | 150 V |

|  |    |
|--|----|
| cUL Recognized  |    |
| mm <sup>2</sup> /AWG/kcmil   | 18 |

## Cable connector - CA-19P1N128008S - 1619478

### Approvals


|                                |       |
|--------------------------------|-------|
| Nominal current I <sub>N</sub> | 5 A   |
| Nominal voltage U <sub>N</sub> | 150 V |

EAC

cULus Recognized

### Drawings

Schematic diagram



Dimensional drawing

