

Product Information

HES8GM Series

8G-Port Din-rail Full Gigabit Managed Ethernet Switches



Features

- RingOn and RingOpen (recovery time < 15ms), RSTP for network redundancy
- SNMPv1/v2c/v3 for network management of different levels
- IGMP snooping and GMRP for filtering multicast traffic
- QoS (IEEE 802.1p/1Q) and TOS/DiffServ to increase determinism
- -40 to +75°C operating temperature range (W models)
- IP30 DIN Rail or Panel Mount



Henrich Electronics Corporation

Main Office

Tel: 860-487-9869

Fax: 860-487-9478

www.henrich-inc.com

Introduction

The HES8GM series is equipped with 8 Gigabit Ports, making it ideal for upgrading an existing network to Gigabit speed or building a new full Gigabit backbone. Gigabit transmission increases bandwidth for higher performance and transfers large amounts of triple-play services across a network quickly. Redundant Ethernet RingOpen, RingOn, RSTP, and MSTP increase system reliability and the availability of your network backbone. The HES8GM series is designed especially for communication demanding applications, such as video and process monitoring, ITS, and DCS systems, all of which can benefit from a scalable backbone construction.

Specifications

Technology		Power Requirements	
Standard :	IEEE802.3, 802.3u, 802.3x, 802.3z	Input Voltage :	12~36VDC @ 24W MAX 10~24VAC @ 24VA MAX
Flow Control :	IEEE802.3x flow control, back pressure flow control	Input Connection :	Grid panel terminal blocks Standard 4 pin input connection (optional)
Protocols :	IGMP Snooping, GMRP, SNMPv1/v2c/v3, DHCP Client, HTTP, HTTPS, Telnet, NTP Client	Physical Characteristics	
	L2 Functions	Case :	Slim Metal Case, IP30 Design
	<ul style="list-style-type: none"> • IEEE 802.1Q Static VLAN and VLAN Label • Link Layer Management Protocol (LLDP) • IEEE 802.1w Rapid Spanning Tree Protocol (RSTP) • IGMP SNOOPING • RingOn™ Redundant Technology, recovery time <15ms • RingOpen Redundancy 	Dimensions :	64.2×183.1×155.1mm
		Installation :	DIN Rail or Panel Mounting
		Environment Limits	
Software functions :	Management Tools	Operating Temp. :	Standard Models: -10 to 60°C Wide Temp. Models: -40 to 75°C
	<ul style="list-style-type: none"> • Web Interface (HTTP and HTTPS) • Console port and Command Line Interface(CLI) controlled by SSHv2 • SNMPv1/v2c/v3 • Flexible configuration and log file management • Managing local file through HTTP, FTP and TFTP • Syslog(System log file and remote syslog server) • SNTP(NTP Client) • Software Online Upgrading 	Storage Temp. :	-40 to 85°C
		Ambient Relative Humidity :	5 to 95%(Non-condensing)
		Standards and Certifications	
Switch Properties		EMI :	FCC Part15, CISPR(EN55022) Class A
MAC Table Size :	16K	EMS :	EN61000-4-2(ESD) Level 3, EN61000-4-3(RS) Level 3, EN61000-4-4(EFT) Level 3, EN61000-4-5(Surge) Level 3, EN61000-4-6(CS) Level 3, EN61000-6-2
Priority Queues :	8	Shock :	IEC 60068-2-27
Max. Number VLANs :	64	Freefall :	IEC 60068-2-32
VLAN ID Range :	VID 1 to 4094	Vibration :	IEC 60068-2-6
IGMP Groups :	256	Warranty	
Interface		Warranty Period :	3 years
Fiber Port :	1000M Gigabit SFP slots.		
LED Indicators :	Power, Port Status, 10/100/1000M		
Output Warning :	Relay, Standard 2 Pin @30V		
Console Port :	RS-232 (RJ45 connector)		

Ordering Information

HES8GM Series

HES8GM-8SFP-VL	Din-rail Managed, 8 x Gigabit SFP Slots, Industrial Temperature -10°C to +60°C, Power Input 12~36VDC or 10~24VAC
HES8GM-8SFP-VLW	Din-rail Managed, 8 x Gigabit SFP Slots, Industrial Wide Temperature -40°C to +75°C, Power Input 12~36VDC or 10~24VAC